



SAFETYNESTS
Stay Safe and Work confidently


PYRAMEX USA

Hydro Dipped

4-Point Ratchet | 12 Variations

- HP44116 • Matte White Graphite Pattern
- HP44116C •• Matte White Graphite Pattern (CSA with clip only)
- HP44116S • Shiny White Graphite Pattern
- HP44117 • Matte Black Graphite Pattern
- HP44117C •• Matte Black Graphite Pattern (CSA with clip only)
- HP44117S • Shiny Black Graphite Pattern
- HP44118 • Matte Copper Graphite Pattern
- HP44119 • Realtree AP® (Matte)
- HP44121 • Matte Red Graphite Pattern
- HP44122 • Matte Blue Graphite Pattern
- HP44123 • Matte Silver Graphite Pattern
- HP44124 • Matte Lime Graphite Pattern



HPRBANDR – Ridgeline Cap Style
and Full Brim Hard Hat Sweat Band



HPR441 – 4-point Ratchet
Replacement Suspension



HPR461 – 6-point Ratchet
Replacement Suspension

Vented Hydro Dipped

4-Point Ratchet | 2 Variations

- HP44116SV • Shiny White Graphite Pattern
- HP44117V • Matte Black Graphite Pattern

Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)

Suspension: high density polyethylene (HDPE) & high impact nylon

Sweat band: polyester fabric & polyurethane (PU) foam

General Specifications

Weight: 358 gm

Shell thickness: 2 - 4 mm

Dimensions: 28 cm x 22 cm x 15.2 cm

Suspension adjust sizing: 6.5 - 8

Suspensions: 4-point & 6-point ratchet

Styles: vented & non-vented

Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15

Types: Type 1

Classes: non-vented Class E, G, and C | vented Class C

Optional features: reverse donning, hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

Markings

Types: Type 1 offers protection to the top of the head

Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection

Tested and marked for reverse orientation

HV: meets all requirements for high visibility

LT: provides protection at low temperatures -22°F

HT: provides protection at high temperatures 140°F

Date code: indicates month and year when the shell was molded – does not indicate service life



Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use

Never alter or modify the shell or suspension system

Inspect the hard hat each time before use and replace if there is ANY sign of damage

Replace hard hat after it receives a considerable impact

Accessories such as liners have not been tested to the requirement of this standard

Clean only with mild soap and lukewarm water

Store hard hat in a clean, dry place that is out of direct sunlight

Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage

REALTREE AP © 2013 of Jordan Outdoor Enterprises, Ltd., all rights reserved.



GOLDEN STAR INTERNATIONAL GENERAL TRADING COMPANY

Al Qibla , Block 8, Building 56, 2nd Floor, Office No.27, Kuwait City

Phone: +965 97242524
E-mail: sales@safetynests.com